



"HK" Electric Heater Kits

NO.	Kit#	Description	Ref. Air Handler use
1	HK052C	5 kW heat strip with single breaker	18,24,30,36,42,48,60
2	HK082C	7.5kW heat strip with single breaker	18,24,30,36,42,48,60
3	HK102C	10 kW heat strip with single breaker	18,24,30,36,42,48,60
4	HK152C	15 kW heat strip with double breaker	36,42,48,60
5	HK202C	20 kW heat strip with double breaker	36,42,48,60

"HK" DATA

Heat Kit Model	Air Handler Model	(kW)Electric Heat	MIN. Circuit Ampacity		MAX.Fuse or Breaker (HACR) Ampacity	
			230	208	230	208
HK052C	18	5	26.7	23.4	30	25
HK082C		7.5	39.8	34.4	40	40
HK102C		10	52.8	45.7	60	50
HK052C	24	5	26.9	23.6	30	25
HK082C		7.5	39.8	34.5	40	40
HK102C		10	52.9	45.8	60	50
HK052C	30	5	26.9	23.6	30	25
HK082C		7.5	39.8	34.5	40	40
HK102C		10	52.9	45.8	60	50
HK052C	36	5	28	24.5	30	25
HK082C		7.5	40.9	35.4	45	40
HK102C		10	54.1	46.8	60	50
HK152C		15	54.1/26	46.8/22.8	60/30	50/25
HK202C		20	54.1/52.1	46.8/45.1	60/60	50/50
HK052C	42	5	28.2	24.7	30	25
HK082C		7.5	41.1	35.5	45	40
HK102C		10	54.2	46.9	60	50
HK152C		15	54.2/26	46.9/22.8	60/30	50/25
HK202C		20	54.2/52.1	46.9/45.1	60/60	50/50
HK052C	48	5	29.4	25.8	30	30
HK082C		7.5	42.3	36.6	45	40
HK102C		10	55.5	48	60	50
HK152C		15	55.5/26	48/22.8	60/30	50/25
HK202C		20	55.5/52.1	48/45.1	60/60	50/50
HK052C	60	5	29.7	26	30	30
HK082C		7.5	42.5	36.8	45	40
HK102C		10	55.7	48.2	60	50
HK152C		15	53/29	46/26	60/30	50/30
HK202C		20	56/53	47/46	60/60	50/50