The AG3000 and Compressor Defender[™] Power Protection Duo

Make the switch to Intermatic for unmatched protection from surges, brownouts and system short cycling.





Today's HVAC equipment is more technologically advanced and expensive; yet, it remains susceptible to damage from poor power quality. 86% of homeowners are at risk of incurring thousands of dollars in replacement costs because their HVAC equipment is not properly protected.



Surges happen. So do brownouts and short cycles. We've got you covered. Meet the dynamic duo of power protection for HVAC equipment: The AG3000 and Compressor Defender[™]

Power disturbances damage air conditioner compressors without warning. Protect vital and expensive air conditioning system components from out-of-warranty coverage caused by power quality issues, such as brownouts, surges and short cycles with a comprehensive solution. Our powerful tag team of the AG3000 and the Compressor Defender[™] provides unsurpassed layered protection from brownouts, surges and short cycles.

Designed with trusted, state-of-the-art TPMOV® (Thermally Protected Metal Oxide Varistor) technology, none can compare to these proven performers! The TPMOV® eliminates the potentially hazardous failure modes that are associated with standard MOV technology.

- Fast, 10-minute or less installation onto disconnect
- Minimize nuisance callbacks to save time and money
- Industry-leading 3-year, \$7,500 connected equipment warranty on compressor and all electronic parts
- Intuitive and easy-to-troubleshoot LED status indicators
- The perfect upsell to seasonal service programs, providing peace-of-mind
- No out-of-warranty costs

AG3000 HVAC Surge Protection

Connects to the furnace/air handler disconnect to protect high-efficiency furnaces,

hydronic heating systems and ductless mini-splits from surges and spikes.

- Unmatched surge protection ratings
- 120/240 VAC single split phase SPD for use on a variety of HVAC equipment
- Green LED protection indicator
- Meets all UL 1449, 4th Edition standards
- Type 4X weatherproof and UV resistant enclosure
- 18 in. 10 gauge leads
- State-of-the-art TPMOV[®] technology

AG3000 Specifications

1												
	Model #	Description	Service Voltage	SPD Type	Nominal Discharge Current	Max. Continuous Operation Voltage	Short Circuit Current Rating	Enclosure				
	AG3000	HVAC Surge	120/240 VAC	1 or 2	10 kA	L-N/G: 150 V, L-L: 300 V	20 kA	Type 4X				

Compressor Defender™ Brownout, Surge and Short Cycle Protection

Installs onto the AC disconnect to protect compressors and circuit boards in residential and light commercial, central AC and heat pump condensing unit applications from surges, brownouts and short cycles.

- 120, 208 and 240 VAC loads
- LED indicators provide real-time status updates for quick and easy troubleshooting
- For use inside condensing units or externally on disconnects
- Complies with ANSI/AHRI Standard 110-2016 Range B for voltage drop protection
- Auto-sense voltage technology 120/208-240 VAC universal input voltage
- Meets ANSI/UL 1449, 4th Edition requirements
- Type 3 weatherproof and UV resistant enclosure
- State-of-the-art TPMOV® technology

Compressor Defender[™] Specifications

Model #	Short Cycle Protection		Service Voltage 120/208-240 VAC						Max. Continuous Operation Voltage		Short Circuit Current Rating	Enclosure
CD1-024R					2	10	kA	L-N/G: 150 V, L-L: 300 V		: 300 V	20 kA	Type 3 Outdoor
					Undervoltage Response Time		Power Disruption Response Time				oltage Protection HRI Standard 110-	2016
	NC 24 VAC			24 VAC NC 5 Line		ŧ.	3-Line Cycles		3 Min.	120	208/230	240
			24 VAC NO						5 101111.	104	180	208

*Typical Response Time

No nonsense 3-year, \$7,500 warranty.

Intermatic's power protection warranty is second to none and goes beyond simply covering electro-mechanical components. We cover all electronic connected equipment parts up to \$7,500. Spend 10 minutes now, save yourself a call-back later. Take the 10-minute challenge: Install one of these protective devices today and see how it can save you time and money.

- Realize an easy upsell to seasonal service programs
- Solidify customer relationships Just a 2% increase in customer retention has the same effect on a contractor's bottom line as cutting cost by 10%.



	ge/Brownout/Short			1 Companyant	
ANS	Model: C			I THE REPORT OF	
	Condition	Green LED	Red LED	-	
2	Surge Protection	ON			
1	No Surge Protection	OFF	•		
	Under Voltage		Flash		
	Short Cycle Protection	Flash	•		
	Unit Power Lost	OFF	OFF		
		NIPPLE SID			
	Une Neut Line T Black White Black Line Line AC Disconnect Load	Typical 200 (940 V	€ UP	e	

Lighting Controls	Surge Protection	Weatherproof	Photo Controls	Timers	Defrost/Refrigeration Controls

Intermatic 7777 Winn Road Spring Grove, IL 60081 (815) 675-7000

©2017 Intermatic 300AG10060



