

KFLIF

SERIES

Klimaïre Model Number			KFUF036-C2G	KFUF048-C2G	KFUF060-C2G
Power supply		V-ph-Hz	208-230/1/60	208-230/1/60	208-230/1/60
Cooling	Capacity	Btu/h	36000	48000	55000
	Input	W	4090	5580	6300
	EER	W/W	2.58	2.52	2.56
Indoor fan motor	Qty		1	2	2
	Input	W	235/200/172	174/157/144	174/157/144
	RLA	A	1.1	1.6	1.6
	Minimum Circuit Ampacity	A	1.4	2	2
	Capacitor	uF	5uF/450V	2.5uF/450V	5uF/450V 2.5
	Speed (Hi/Med/Lo)	rpm	1320/1175/1050	1400/1220/1090	1400/1220/1090
Indoor coil	Number of rows	n	2	2	3
	Coil length x height x width	in	36.8x11.6x1.05	51.2x11.6x1.05	51.2x11.6x1.6
	Number of circuits	n	6	8	8
Indoor air flow (Hi/Med/Lo)		cfm	1059/942/794	1354/1118/1000	1354/1118/1000
Indoor noise level (sound pressure) (Hi/Med/Lo)		dB(A)	55/51/48	56/52/48	56/52/48
Throttle type		Type	Bullet 0.068	Bullet 0.078	Bullet 0.080
Indoor unit	Dimension (WxDxH)	in	50.6x26.6x9.25	65x26.6x9.25	65x26.6x9.25
	Packing (WxDxH)	in	53.5x28.7x12.3	67.9x29.7x12.3	67.9x29.7x12.3
	Net/Gross weight	lb	70.4/81.4	81.4/94.6	85.8/99
Design pressure		psi	609/218	609/218	609/218
Drainage water pipe diameter		in	OD Φ 1"	OD Φ 1"	OD Φ 1"
Refrigerant piping Liquid side/Gas side		in	3/8"/3/4"	3/8"/3/4"	3/8"/3/4"
Controller		Type	Remote control	Remote control	Remote control
Operation temperature		°F	63 - 86	63 - 86	63 - 86
Room temperature Cooling		°F	63 - 90	63 - 90	63 - 90

Note: The data in this technical specifications may be changed without notice for further improvement on quality and performance

